

ELECTRICAL SPECIFICATION

Nominal Diameter	385mm/ 15 inch
Frame	Iron
Magnet	Ferrite Ring
Magnet Diameter	190mm
Nominal Impedance	8 Ohm
Magnetic Gap Depth	8mm
AES Power Handling	400W
Continuous Program Power	800W
Sensitivity 1W/ 1M	99.2db
Frequency Range	53- 3.1kHz
Voice Coil Diameter	75.5mm/ 2.9 inch
Winding Material	Copper
Former Material	Aluminium
Winding Depth	16.8mm
Surround (Damper)	Chemical Fiber
Cone and Dust Cap	Paper
Surround Material	Polycotton
Surround Design	Double-roll

THIELE & SMALL PARAMETERS

Rosonanco Frequency	Fs	53hz
DC Resistance	Re	6 Ω
Mechanical Factor	Qms	1.68
Electrical Factor	Qes	0.41
Total Factor	Qts	0.33
BL Factor	BL	19.3T.m
Effective Moving Mass	Mms	76.9gr
Compliance	Cms	116.6 μ M/N
Equivalent Cas Air Load	Vas	148L
Effective Piston Area	Sd	94m²
η (Eta Zero)	η 0	5.20%

MOUNTING & SHIPPING INFORMATION

Overall Diameter	385mm
Bolt Circle Diameter	377mm
Baffle Cutout Diameter	361mm
Depth	155mm
Net Weight	6.3kg

