

ELECTRICAL SPECIFICATION

Nominal Diameter	210mm/ 8 inch
Frame	Iron
Magnet	Ferrite Ring
Magnet Diameter	120mm
Nominal Impedance	8 Ohm
Magnetic Gap Depth	4mm
Power RMS	160W
Sensitivity 1W/ 1M	91.2db
Frequency Range	61- 4.8kHz
Voice Coil Diameter	35.5mm/ 1.3 inch
Winding Material	Copper
Former Material	Aluminium
Winding Depth	14mm
Surround (Damper)	Cotton
Cone and Dust Cap	Paper
Surround Material	Polycotton
Surround Design	One-roll

THIELE & SMALL PARAMETERS

Rosonanco Frequency	Fs	61hz
DC Resistance	Re	6 Ω
Mechanical Factor	Qms	2.5
Electrical Factor	Qes	0.67
Total Factor	Qts	0.53
BL Factor	BL	9T.m
Effective Moving Mass	Mms	24.1gr
Compliance	Cms	281.1 μ M/N
Equivalent Gas Air Load	Vas	25L
Effective Piston Area	Sd	25.4m ²
η (Eta Zero)	η 0	0.80%

MOUNTING & SHIPPING INFORMATION

Overall Diameter	210mm
Bolt Circle Diameter	202mm
Baffle Cutout Diameter	182mm
Depth	95mm
Net Weight	1.72kg

