

ELECTRICAL SPECIFICATION

| | |
|---------------------|------------------|
| Nominal Diameter | 306mm/ 12 inch |
| Frame | Iron |
| Magnet | Ferrite Ring |
| Magnet Diameter | 140mm |
| Nominal Impedance | 8 Ohm |
| Magnetic Gap Depth | 6mm |
| Power RMS | 200W |
| Sensitivity 1W/ 1M | 93.5db |
| Frequency Range | 49- 1.8kHz |
| Voice Coil Diameter | 49.5mm/ 1.9 inch |
| Winding Material | Copper |
| Former Material | Aluminium |
| Winding Depth | 17.3mm |
| Surround (Damper) | Cotton |
| Cone and Dust Cap | Paper |
| Surround Material | Polycotton |
| Surround Design | Triple-roll |

THIELE & SMALL PARAMETERS

| | | |
|-------------------------|-----|-----------|
| Rosonanco Frequency | Fs | 49hz |
| DC Resistance | Re | 6.5 Ω |
| Mechanical Factor | Qms | 2.272 |
| Electrical Factor | Qes | 0.801 |
| Total Factor | Qts | 0.592 |
| BL Factor | BL | 11.6T.m |
| Effective Moving Mass | Mms | 53gr |
| Compliance | Cms | 192 μ M/N |
| Equivalent Cas Air Load | Vas | 96L |
| Effective Piston Area | Sd | 59m² |
| η (Eta Zero) | η 0 | 1.40% |

MOUNTING & SHIPPING INFORMATION

| | |
|------------------------|--------|
| Overall Diameter | 306mm |
| Bolt Circle Diameter | 300mm |
| Baffle Cutout Diameter | 282mm |
| Depth | 128mm |
| Net Weight | 2.95kg |

